

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 May 2001 (31.05.2001)

PCT

(10) International Publication Number  
**WO 01/39508 A1**

(51) International Patent Classification<sup>7</sup>: H04N 7/58, 7/24

(21) International Application Number: PCT/GB00/04520

(22) International Filing Date:  
27 November 2000 (27.11.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
9928023.2 26 November 1999 (26.11.1999) GB

(71) Applicant (for all designated States except US): **BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY** [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).

Masoomeh [GB/GB]; 5 Jewell View, Kesgrave, Ipswich IP5 2YA (GB). GHANBARI, Mohammed [GB/GB]; 14 Crome Close, Colchester, Essex CO3 4QQ (GB). ROSDIANA, Eva [ID/SG]; Heritage View Condominium, Tower B, 10 Dover Rise, 06-10, Singapore 138680 (SG).

(74) Agent: LLOYD, Barry, George, William; BT Group Legal Services, Intellectual Property Department, Holborn Centre, 8th Floor, 120 Holborn, London EC1N 2TE (GB).

(81) Designated States (national): CA, US.


(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:  
— With international search report.

(72) Inventors; and  
(75) Inventors/Applicants (for US only): **AZMOODEH,**

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VIDEO TRANSMISSION



(57) Abstract: The invention concerns the control of Asynchronous Transfer Mode (ATM), or other systems, using available bit rate (ABR) transmission. A source of data is permitted to transmit at a data rate which is set by the network according to the available capacity. Where television pictures are being transmitted, the actual data rate can be controlled by varying the degree of compression applied by video coder (or transcoder). Existing procedures for dividing up the available capacity between competing video sources are found to be unsatisfactory in terms of achieving equal picture quality for each source. In the invention, each source calculates a measure of picture complexity, and the network (for example, an ATM switch) uses the means to calculate how the capacity should be shared.

WO 01/39508 A1

## Video Transmission

The present invention is concerned with the transmission of video signals via telecommunications links, and more particularly with transmission via systems such as available bit rate (ABR) systems where available capacity is monitored and the allocation of capacity among a number of sources adjusted accordingly.

ABR is one of several types of services used in ATM (asynchronous transfer mode) networks. An ATM switch receiving from a number of sources periodically signals the allowable transmission rate back to the sources using control cells called resource management (RM) cells. Several bandwidth allocation algorithms for ABR have been proposed (see The ATM Forum Technical Committee: "Traffic Management Specification version 4.0", April 1996), one of which, called Explicit Rate Indication for Congestion Avoidance (ERICA), involves dynamically varying the allocation to a source in dependence on the pre-existing rate at which that source is transmitting.

These algorithms are designed to achieve an equitable distribution of available capacity among competing sources. However, in the case of video signals, they can suffer from the drawback that as picture content varies, some suffer a reduction in picture quality whilst others may maintain a quality well above a subjectively acceptable level.

According to one aspect of the invention there is provided a system for transmission of video signals comprising:

a plurality of video interfaces each operable to receive an input video signal and to delivering encoded video data at a controllable rate; and

an output interface connected to receive video data from the video interfaces and to deliver said data to a communications link;

wherein each video interface includes means operable to compute a measure of the complexity of the video signals and to transmit it to the output interface; and

the output interface includes control means operable to receive said measures, to compute for each source, in dependence upon the measures and the available capacity of the link, a permitted rate, and to transmit to each video interface a signal indicating the permitted rate for that interface.

The video interface could be a video encoder for receiving analogue or digital video signals, or a transcoder for receiving digitally encoded video signals and delivering digitally encoded signals in the same (or different) format at a controllable rate.

5 The output interface could be a simple multiplexer, or may be a telecommunications switch, for example an ATM switch. If desired the switch could also receive inputs from other feeds whose bit rates are not subject to control (i.e. fixed rate or variable rate). In such a case the available capacity is the actual link capacity less the demand from these other feeds.

Some embodiments of the invention will now be described, by way of  
10 example, with reference to the accompanying drawings.

In Figure 1, an ATM switch 1 receives inputs from a plurality N of video transcoders 2 each of which receives video signals at a respective input 3. The switch 1 may also have further inputs 4 for video or other signals from fixed or variable rate sources. The output of the switch connects to a telecommunications  
15 network at 6.

The encoders 2 receive and deliver signals in accordance with the MPEG standard defined by ISO 11172.

The encoder is conventional except that:

- (a) it periodically computes a picture complexity measure which it  
20 transmits to the switch 4;
- (b) it receives from the switch 4 periodic signals indicating the data rate at which it is permitted to transmit.

Figure 2 is a simplified block diagram of a MPEG to MPEG transcoder. Received signals first pass through a variable length decoder 10, then an inverse quantiser 11  
25 to produce DCT transform coefficients. These are then requantised in a quantiser 12, recoded by a variable length code at 13, and fed to an output buffer 14. Because the data rate at this point varies according to picture content, a buffer control unit 15 monitors the buffer fullness and controls the quantiser 12 so that the buffer 14 can output at a desired rate without overflow or underflow.

30 The output of the quantiser 12 is processed by an inverse quantiser 16 and then subtracted at 17 from the output of the quantiser 11 to produce an error signal representing the error introduced by the requantisation at 12. This is converted into pixel error values, by an inverse DCT stage 18, motion compensation 19-21 and then

by the DCT again at 22 to form a motion-compensated error signal which is added into the next frame in an adder 23 to correct any tendency for errors to propagate. This error control is conventional.

The complexity measure is, in this version of the invention, a complexity index C defined as follows:

$$C = \sum_{i=1}^N \frac{B_i Q_i}{2}$$

where  $B_i$  is the number of bits used to encode frame  $i$  and  $Q_i$  is the average quantiser step size used to encode frame  $i$ . The divisor '2' is not essential, but used simply because in standard MPEG, quantiser step sizes are always even numbers. The summation is over  $N$  frames where  $N$  is the number of frames (typically 12) in a "Group of Pictures" as defined by the standard. We prefer to sum, rather than use the instantaneous value, to give a degree of smoothing to the operation of the system; however this is not essential. This value could be calculated once every  $N$  frames, however we prefer to calculate it every frame over a sliding window: i.e.

$$C_j = \sum_{i=j}^{j+N-1} \frac{B_i Q_i}{2}$$

In the case of an MPEG encoder or MPEG output transcoder the product  $B_i Q_i$  is conventionally calculated within the buffer control 6 for the purpose of balancing the allocation of bits among the different types (I, P and B) of frame, see, for example, M Ghanbari "Video Coding - an introduction to standard encoders" IEE, London, 1999, p. 110-111. Thus the modified encoder, or transcoder requires the additional step for performing the summation, shown in Figure 2 as a summation unit 24, though in practice it would be more convenient to implement it as additional step of a stored program controlled processor implementing the function of the control unit 15.

The values of  $B$  and  $Q$  are those at the input - i.e. at the input to the variable length decoder 10 (the received signal of course contains the value of  $Q$  for controlling the inverse quantiser 11). However, if desired, these values could both be

measured at the output, i.e.  $B_i$  is the number of bits performed at the output of the variable length coder and  $Q_i$  is the average step size used by the quantiser 13. Naturally the result is very similar. In the case of an encoder, the values at the output would be used.

- 5 In MPEG, the quantisation step size is set once for each macro block into which a frame is divided: the average step size is thus the sum of the individual values divided by the number of macro blocks per frame.

As for the rate control, a receiver 24 is provided which receives rate control signals R periodically and transfers these to the control unit 16 where it changes the  
10 target data rate which the buffer/quantiser control algorithm operate to. The control unit is otherwise conventional.

The output of the encoder is formatted into standard ATM format at 25. It will be understood that the complexity indices  $C_i$  and the rate parameter R are carried in control cells (referred to as 'RM' cells) of the ATM signal.

- 15 Turning now to the ATM switch 1, this is conventional except as follows. This calculates, as is conventional, the capacity it has available on its link to the network 6, less any capacity that may be required by the inputs 4, and multiplies this by a target utilisation factor, typically 0.9 or 0.95, to give a target ABR capacity T. This capacity is distributed among the sources 2 in proportion to the complexity  
20 measures  $C_i$  received - i.e., for source k of K sources:

$$R(k) = \frac{C_j(k)}{\sum_{k=1}^K C_j(k)}$$

The resultant permitted rate parameters  $R(k)$  are transmitted back to the respective sources 2 in the RM cells of the ATM signals.

- 25 This algorithm is similar to, but rather simpler than, conventional ABR rate control in ATM switches such as that described in Section 1.5 of the above-mentioned ATM specification.

Experiments have been carried out to compare the performance of this arrangement with the known ERICA rate allocation method. Three ABR video  
30 sources, classified as easy, medium and difficult, were MPEG CBR pre-encoded at different bit rates to produce acceptable picture quality. They were transmitted over

a network using the arrangement as depicted in Figure 1. For simplicity, no high priority CBR or VBR services were included in the simulation. The experiments were carried out separately for both the ERICA and the picture complexity-based rate allocation (PCBRA) algorithm described above, and the picture quality of the ABR sources were compared at the destination. Table 1 shows the parameters of both experiments. The link rate of the switch's output port was set to the sum of the ABR sources' encoded rates, i.e. 8.1 Mbit/sec (100% loading). With this service rate, there will be compression required from time to time as the rate of the MPEG video varies within the frames of a GoP.

10

ABR Source	Picture content	Mean bit rate Mbit/s	Peak Cell Rate (PCR) Mbit/s	Minimum Cell Rate (MCR) Mbit/s
1	easy (news)	0.694	2.75	0.208
2	medium (drama)	1.04	3.35	0.312
3	difficult (mobile)	6.37	15.78	1.9

Table 1: Simulation Parameters

The objective performance measurements for the picture quality used in this study is the Peak-to-peak Signal-to-Noise Ratio (PSNR).

Figures 3 to 5 show the picture quality of the ABR sources at the switch output. PSNR comparisons between ERICA and PCBRA algorithms for the easy, medium and difficult video sequences are shown in figures 3, 4 and 5 respectively. For the ERICA algorithm, ABR sources 1 and 2, easy and medium respectively, have unnecessarily high PSNR while ABR source 3, the difficult sequence, has poor quality. When using complexity-based algorithm, the easy and medium sources have lower quality compared to the ERICA cases but still maintain a subjectively satisfactory level. Conversely, the difficult video has much better quality than the one in ERICA. In other words, the picture complexity based rate allocation algorithm assures fairer picture quality among the sources than the ERICA model.

It has already been mentioned that the application for the invention is not limited to ATM systems. It can, for example, be applied to any network that can

feed back network congestion to the source. Also, the particular picture complexity index is not the only measure of picture complexity that can be used. For example, rather than averaging  $Q_i$ , one could form the  $B_i Q_i$  product for each macro block and sum these products for the whole frame.

- 5        This approach assumes the use of a picture-content compression algorithm which generates picture data at a variable rate by controlling the number of quantisation levels used. Thus the measure which is being formed is, in a sense, a measure of the data rate that would have been generated by an encoder had it been free to choose the rate appropriate to the prevailing picture content. So if rate
- 10 control operates (instead or as well) by means other than controlling the quantisation step size (which reduces the signal to noise ratio) – for example by pixel subsampling or discarding of transform coefficients (which reduce the spatial resolution) these could also be taken into account in forming the complexity measure.

## CLAIMS

1. A system for transmission of video signals comprising:  
a plurality of video interfaces each operable to receive an input video signal  
5 and to delivering encoded video data at a controllable rate; and  
an output interface connected to receive video data from the video interfaces  
and to deliver said data to a communications link;  
wherein each video interface includes means operable to compute a measure  
of the complexity of the video signals and to transmit it to the output interface; and  
10 the output interface includes control means operable to receive said  
measures, to compute for each source, in dependence upon the measures and the  
available capacity of the link, a permitted rate, and to transmit to each video interface  
a signal indicating the permitted rate for that interface.
- 15 2. A system according to claim 1 in which the complexity measure is formed as  
a function of (a) the number of bits generated by the video interface and (b) a factor  
indicative of the degree to which the number of bits has been reduced as a result of  
rate control.
- 20 3. A system according to claim 2 in which the measure of complexity of the  
video signals is formed by calculating for each frame of the video signals the product  
of the number of bits used to encode that frame and the average quantiser step size  
used for coding that frame.
- 25 4. A system for transmission of video signals substantially as described herein  
with reference to the accompanying drawings.



Fig.1.





Fig.3.






Fig.4.





Fig.5.



# INTERNATIONAL SEARCH REPORT

Int'l Application No  
**PCT/GB 00/04520**

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 H04N7/58 H04N7/24

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)  
EPO-Internal, INSPEC, COMPENDEX

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	KEESMAN G: "MULTI-PROGRAM VIDEO COMPRESSION USING JOINT BIT-RATE CONTROL" PHILIPS JOURNAL OF RESEARCH, NL, ELSEVIER, AMSTERDAM, vol. 50, no. 1/02, 1 July 1996 (1996-07-01), pages 21-45, XP000627660 ISSN: 0165-5817 paragraph '04.1! figure 9	1-4

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "S" document member of the same patent family

Date of the actual completion of the international search

20 February 2001

Date of mailing of the international search report

27/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl  
Fax: (+31-70) 340-3016

Authorized officer

Berbain, F

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/GB 00/04520

**C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>SWANG L ET AL: "JOINT RATE CONTROL FOR MULTI-PROGRAM VIDEO CODING" IEEE TRANSACTIONS ON CONSUMER ELECTRONICS,US,IEEE INC. NEW YORK, vol. 42, no. 3, 1 August 1996 (1996-08-01), pages 300-305, XP000638506 ISSN: 0098-3063 paragraph '02.2! figure 3</p>	1-4
A	<p>EP 0 550 843 A (GEN INSTRUMENT CORP) 14 July 1993 (1993-07-14) abstract figure 1</p>	1-4
A	<p>GUHA A ET AL: "MULTICHANNEL JOINT RATE CONTROL OF VBR MPEG ENCODED VIDEO FOR DBS APPLICATIONS" IEEE TRANSACTIONS ON CONSUMER ELECTRONICS,US,IEEE INC. NEW YORK, vol. 40, no. 3, 1 August 1994 (1994-08-01), pages 616-623, XP000471227 ISSN: 0098-3063 figure 1 paragraph '0III!</p>	1-4

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/04520

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0550843 A	14-07-1993	US 5216503 A	01-06-1993
		AT 183354 T	15-08-1999
		AU 650219 B	09-06-1994
		AU 2995592 A	01-07-1993
		CA 2084178 A,C	25-06-1993
		DE 69229773 D	16-09-1999
		DE 69229773 T	02-03-2000
		ES 2134786 T	16-10-1999
		HK 1013758 A	19-05-2000
		JP 2000032454 A	28-01-2000
		JP 2986039 B	06-12-1999
		JP 6086261 A	25-03-1994
		KR 9613654 B	10-10-1996
		MX 9207549 A	31-05-1994
		NO 302210 B	02-02-1998